

〈銅〉C1220 パイプ (DCU)

- ・直管＝ H or 1/2H 軟管＝ O
- ・P（りん）を 0.015 ～ 0.040%添加された純銅です。
水素脆化の心配もなく、耐食性・絞り加工性・溶接性・熱伝導性に優れた材質です。

■直管

材質	調質	径		肉厚	長さ	
C1220	H	φ 3	×	t0.5	×	5000
C1220	1/2H	φ 4	×	t0.5	×	5000
C1220	1/2H	φ 4	×	t0.8	×	5000
C1220	1/2H	φ 4	×	t1.0	×	5000
C1220	1/2H	φ 5	×	t0.5	×	5000
C1220	1/2H	φ 5	×	t0.8	×	5000
C1220	1/2H	φ 5	×	t1.0	×	5000
C1220	1/2H	φ 6	×	t0.5	×	5000
C1220	1/2H	φ 6	×	t0.8	×	5000
C1220	1/2H	φ 6	×	t1.0	×	5000
C1220	1/2H	φ 6	×	t1.2	×	5000
C1220	1/2H	φ 6	×	t1.5	×	5000
C1220	1/2H	φ 6.4	×	t1.0	×	5000
C1220	1/2H	φ 8	×	t0.8	×	5000
C1220	1/2H	φ 8	×	t1.0	×	5000
C1220	1/2H	φ 8	×	t1.2	×	5000
C1220	1/2H	φ 8	×	t1.4	×	5000
C1220	1/2H	φ 8	×	t1.5	×	5000
C1220	1/2H	φ 8	×	t2.0	×	5000
C1220	1/2H	φ 9.5	×	t0.8	×	5000
C1220	1/2H	φ 9.5	×	t1.0	×	5000
C1220	1/2H	φ 9.5	×	t1.2	×	5000
C1220	H	φ 9.5	×	t1.6	×	5000
C1220	1/2H	φ 10	×	t0.8	×	5000
C1220	1/2H	φ 10	×	t1.0	×	5000
C1220	1/2H	φ 10	×	t1.2	×	5000
C1220	1/2H	φ 10	×	t1.4	×	5000
C1220	1/2H	φ 10	×	t1.5	×	5000
C1220	1/2H	φ 10	×	t1.6	×	5000
C1220	1/2H	φ 10	×	t2.0	×	5000
C1220	1/2H	φ 12	×	t1.0	×	5000
C1220	1/2H	φ 12	×	t1.2	×	5000
C1220	1/2H	φ 12	×	t1.4	×	5000
C1220	1/2H	φ 12	×	t1.5	×	5000

材質	調質	径		肉厚	長さ	
C1220	1/2H	φ 12	×	t1.6	×	5000
C1220	1/2H	φ 12	×	t2.0	×	5000
C1220	H	φ 12	×	t3.0	×	5000
C1220	1/2H	φ 12.7	×	t0.8	×	5000
C1220	1/2H	φ 12.7	×	t1.0	×	5000
C1220	1/2H	φ 12.7	×	t1.2	×	5000
C1220	1/2H	φ 12.7	×	t1.5	×	5000
C1220	H・1/2H	φ 12.7	×	t2.0	×	5000
C1220	1/2H	φ 14	×	t1.0	×	5000
C1220	1/2H	φ 14	×	t1.6	×	5000
C1220	1/2H	φ 14	×	t2.0	×	5000
C1220	1/2H	φ 15	×	t1.0	×	5000
C1220	1/2H	φ 15	×	t1.2	×	5000
C1220	1/2H	φ 15	×	t1.5	×	5000
C1220	1/2H	φ 15	×	t1.6	×	5000
C1220	1/2H	φ 15	×	t2.0	×	5000
C1220	1/2H	φ 15.9	×	t0.7	×	5000
C1220	1/2H	φ 15.9	×	t0.8	×	5000
C1220	1/2H	φ 15.9	×	t1.0	×	5000
C1220	1/2H	φ 15.9	×	t1.2	×	5000
C1220	1/2H	φ 15.9	×	t1.5	×	5000
C1220	1/2H	φ 15.9	×	t1.6	×	5000
C1220	1/2H	φ 15.9	×	t2.0	×	5000
C1220	1/2H	φ 16	×	t1.0	×	5000
C1220	1/2H	φ 16	×	t1.2	×	5000
C1220	1/2H	φ 16	×	t1.5	×	5000
C1220	1/2H	φ 16	×	t1.6	×	5000
C1220	1/2H	φ 16	×	t2.0	×	5000
C1220	H	φ 17.3	×	t2.3	×	5000
C1220	1/2H	φ 18	×	t1.0	×	5000
C1220	1/2H	φ 18	×	t1.5	×	5000
C1220	1/2H	φ 18	×	t1.6	×	5000
C1220	1/2H	φ 18	×	t2.0	×	5000
C1220	1/2H	φ 18	×	t2.5	×	5000

当社取扱商品・加工品などのお問い合わせは下記までお気軽にご連絡ください。

株式会社稲垣商店

INAGAKI-SHOUTEN Co., Ltd

〒 550-0015 大阪市西区南堀江 4 丁目 14 番 19 号

TEL：06-6531-2456（代表） FAX：06-6541-3198

E-mail：info@inagaki-shouten.jp <https://www.inagaki-shouten.jp>

2025.08

〈銅〉 C1220 パイプ (DCU)

■直管

材質	調質	径	肉厚	長さ
C1220	1/2H	φ 19.05 ×	t0.7 ×	5000
C1220	1/2H	φ 19.05 ×	t0.8 ×	5000
C1220	1/2H	φ 19.05 ×	t1.0 ×	5000
C1220	1/2H	φ 19.05 ×	t1.2 ×	5000
C1220	1/2H	φ 19.05 ×	t1.5 ×	5000
C1220	1/2H	φ 19.05 ×	t1.6 ×	5000
C1220	1/2H	φ 19.05 ×	t2.0 ×	5000
C1220	1/2H	φ 19.05 ×	t2.5 ×	5000
C1220	1/2H	φ 20 ×	t1.0 ×	5000
C1220	1/2H	φ 20 ×	t1.2 ×	5000
C1220	1/2H	φ 20 ×	t1.5 ×	5000
C1220	1/2H	φ 20 ×	t1.6 ×	5000
C1220	1/2H	φ 20 ×	t1.8 ×	5000
C1220	1/2H	φ 20 ×	t2.0 ×	5000
C1220	1/2H	φ 20 ×	t2.5 ×	5000
C1220	1/2H	φ 20 ×	t3.0 ×	5000
C1220	H	φ 21.7 ×	t2.6 ×	5000
C1220	1/2H	φ 22 ×	t1.5 ×	5000
C1220	1/2H	φ 22 ×	t2.0 ×	5000
C1220	1/2H	φ 22 ×	t3.0 ×	5000
C1220	1/2H	φ 22 ×	t3.5 ×	5000
C1220	1/2H	φ 22 ×	t4.0 ×	5000
C1220	1/2H	φ 22.2 ×	t1.0 ×	5000
C1220	1/2H	φ 22.2 ×	t1.2 ×	5000
C1220	1/2H	φ 22.2 ×	t1.5 ×	5000
C1220	1/2H	φ 25 ×	t1.6 ×	5000
C1220	1/2H	φ 25 ×	t2.0 ×	5000
C1220	1/2H	φ 25 ×	t2.5 ×	5000
C1220	1/2H	φ 25 ×	t3.0 ×	5000
C1220	1/2H	φ 25.4 ×	t0.8 ×	5000
C1220	1/2H	φ 25.4 ×	t1.0 ×	5000
C1220	1/2H	φ 25.4 ×	t1.6 ×	5000
C1220	1/2H	φ 25.4 ×	t2.0 ×	5000
C1220	1/2H	φ 25.4 ×	t3.0 ×	5000
C1220	1/2H	φ 28 ×	t1.6 ×	5000
C1220	H・1/2H	φ 28.5 ×	t1.0 ×	5000

材質	調質	径	肉厚	長さ
C1220	1/2H	φ 28.5 ×	t1.6 ×	5000
C1220	1/2H	φ 30 ×	t1.5 ×	5000
C1220	1/2H	φ 30 ×	t1.6 ×	5000
C1220	1/2H	φ 30 ×	t2.0 ×	5000
C1220	1/2H	φ 30 ×	t2.5 ×	5000
C1220	1/2H	φ 30 ×	t3.0 ×	5000
C1220	H	φ 31.8 ×	t1.0 ×	5000
C1220	1/2H	φ 31.8 ×	t1.6 ×	5000
C1220	1/2H	φ 31.8 ×	t2.0 ×	5000
C1220	1/2H	φ 31.8 ×	t3.0 ×	5000
C1220	1/2H	φ 32 ×	t2.0 ×	5000/6000
C1220	1/2H	φ 32 ×	t2.5 ×	5000
C1220	1/2H	φ 32 ×	t3.0 ×	5000
C1220	H・1/2H	φ 34 ×	t2.0 ×	5000
C1220	1/2H	φ 34 ×	t3.0 ×	5000
C1220	H	φ 35 ×	t1.2 ×	5000
C1220	1/2H	φ 35 ×	t1.6 ×	5000
C1220	1/2H	φ 35 ×	t2.0 ×	5000
C1220	1/2H	φ 35 ×	t2.5 ×	5000
C1220	1/2H	φ 35 ×	t3.0 ×	5000
C1220	1/2H	φ 35 ×	t4.0 ×	5000
C1220	1/2H	φ 38 ×	t3.0 ×	5000
C1220	1/2H	φ 38.1 ×	t1.2 ×	5000
C1220	1/2H	φ 38.1 ×	t2.0 ×	5000
C1220	1/2H	φ 38.1 ×	t3.0 ×	5000
C1220	H	φ 40 ×	t1.5 ×	5000
C1220	1/2H	φ 40 ×	t2.0 ×	5000
C1220	1/2H	φ 40 ×	t3.0 ×	5000
C1220	H	φ 40 ×	t4.0 ×	5000
C1220	H	φ 41.28 ×	t1.24 ×	5000
C1220	1/2H	φ 42.7 ×	t3.0 ×	5000
C1220	1/2H	φ 42.7 ×	t3.5 ×	5000
C1220	H	φ 42.7 ×	t4.5 ×	5000
C1220	1/2H	φ 45 ×	t2.0 ×	5000
C1220	H・1/2H	φ 45 ×	t2.5 ×	5000
C1220	1/2H	φ 45 ×	t3.0 ×	5000

当社取扱商品・加工品などのお問い合わせは下記までお気軽にご連絡ください。

株式会社稲垣商店
INAGAKI-SHOUTEN Co., Ltd

〒 550-0015 大阪市西区南堀江 4 丁目 14 番 19 号
TEL : 06-6531-2456 (代表) FAX : 06-6541-3198
E-mail : info@inagaki-shouten.jp <https://www.inagaki-shouten.jp>

2025.08

〈銅〉 C1220 パイプ (DCU)

■直管

材質	調質	径		肉厚	長さ	
C1220	1/2H	φ 45	×	t4.0	×	5000
C1220	1/2H	φ 48.6	×	t3.0	×	5000
C1220	H・1/2H	φ 48.6	×	t3.5	×	5000
C1220	H	φ 48.6	×	t4.0	×	5100
C1220	1/2H	φ 50	×	t3.0	×	5000
C1220	H	φ 50.8	×	t1.2	×	5000
C1220	H	φ 50.8	×	t1.5	×	5000
C1220	1/2H	φ 50.8	×	t2.0	×	5000
C1220	1/2H	φ 50.8	×	t3.0	×	5000
C1220	1/2H	φ 55	×	t2.0	×	5000
C1220	1/2H	φ 55	×	t2.5	×	5000
C1220	H・1/2H	φ 57	×	t3.0	×	5000
C1220	1/2H	φ 60	×	t3.0	×	5000
C1220	H	φ 63.5	×	t3.0	×	5000
C1220	1/2H	φ 70	×	t3.0	×	5000
C1220	H	φ 73	×	t3.0	×	5000

当社取扱商品・加工品などのお問い合わせは下記までお気軽にご連絡ください。

〈銅〉 C1220 パイプ (DCU)

■軟管

材質	調質	径	肉厚	長さ
C1220	OL	φ 2	×	t0.5 × 300 m
C1220	O	φ 4	×	t0.6 × 10 m
C1220	O	φ 4	×	t1.0 × 10 m
C1220	O	φ 4.8	×	t0.8 × 10 m / 50 m
C1220	O	φ 5	×	t0.8 × 10 m
C1220	O	φ 5	×	t1.0 × 10 m
C1220	O	φ 6	×	t0.8 × 10 m / 20 m
C1220	O	φ 6	×	t1.0 × 5 m / 10 m / 20 m / 30 m / 50 m
C1220	O	φ 6	×	t1.2 × 30 m
C1220	O	φ 6	×	t1.5 × 30 m
C1220	O	φ 6.4	×	t0.8 × 20 m
C1220	O	φ 6.4	×	t1.0 × 3 m / 5 m / 20 m
C1220	O	φ 8	×	t0.8 × 10 m / 20 m
C1220	O	φ 8	×	t1.0 × 5 m / 10 m / 20 m / 30 m / 50 m
C1220	O	φ 8	×	t1.2 × 30 m
C1220	O	φ 8	×	t1.5 × 30 m / 50 m
C1220	O	φ 8	×	t2.0 × 20 m
C1220	O	φ 9.5	×	t0.8 × 20 m
C1220	O	φ 9.5	×	t1.0 × 20 m
C1220	O	φ 9.5	×	t1.2 × 20 m
C1220	O	φ 10	×	t0.8 × 20 m
C1220	O	φ 10	×	t1.0 × 5 m / 10 m / 20 m / 30 m / 50 m
C1220	O	φ 10	×	t1.2 × 30 m
C1220	O	φ 10	×	t1.4 × 30 m
C1220	O	φ 10	×	t1.5 × 30 m
C1220	O	φ 10	×	t1.6 × 30 m
C1220	O	φ 10	×	t2.0 × 30 m
C1220	O	φ 12	×	t1.0 × 10 m / 20 m / 30 m / 50 m
C1220	O	φ 12	×	t1.2 × 20 m / 30 m
C1220	O	φ 12	×	t1.5 × 30 m
C1220	O	φ 12	×	t1.6 × 30 m
C1220	O	φ 12	×	t2.0 × 30 m
C1220	O	φ 12.7	×	t0.8 × 20 m
C1220	O	φ 12.7	×	t1.0 × 20 m
C1220	O	φ 12.7	×	t1.2 × 20 m
C1220	O	φ 12.7	×	t1.5 × 30 m

材質	調質	径	肉厚	長さ
C1220	O	φ 14	×	t1.0 × 10 m
C1220	O	φ 14	×	t1.5 × 20 m
C1220	O	φ 15	×	t1.0 × 10 m / 20 m
C1220	O	φ 15	×	t1.2 × 20 m / 30 m
C1220	O	φ 15	×	t1.5 × 30 m
C1220	O	φ 15	×	t1.6 × 30 m
C1220	O	φ 15	×	t2.0 × 30 m
C1220	O	φ 15.9	×	t1.0 × 20 m
C1220	O	φ 15.9	×	t1.2 × 20 m
C1220	O	φ 15.9	×	t1.5 × 30 m
C1220	O	φ 16	×	t2.0 × 30 m
C1220	O	φ 19.05	×	t1.0 × 20 m
C1220	O	φ 19.05	×	t1.5 × 30 m
C1220	O	φ 20	×	t2.0 × 20 m

当社取扱商品・加工品などのお問い合わせは下記までお気軽にご連絡ください。

株式会社稲垣商店
INAGAKI-SHOUTEN Co., Ltd

〒 550-0015 大阪市西区南堀江 4 丁目 14 番 19 号
TEL : 06-6531-2456 (代表) FAX : 06-6541-3198
E-mail : info@inagaki-shouten.jp <https://www.inagaki-shouten.jp>

2025.08

〈銅〉 C1220 パイプ (DCU)

■コントロール銅管

材質	調質	径	肉厚	長さ	備考
C1220	O	φ 6	× t1	× 300 m	被覆 1.0mm 付き
C1220	O	φ 8	× t1	× 300 m	被覆 1.1mm 付き
C1220	O	φ 10	× t1	× 300 m	被覆 1.1mm 付き
C1220	O	φ 12	× t1	× 300 m	被覆 1.1mm 付き

当社取扱商品・加工品などのお問い合わせは下記までお気軽にご連絡ください。

株式会社稲垣商店
INAGAKI-SHOUTEN Co., Ltd

〒 550-0015 大阪市西区南堀江 4 丁目 14 番 19 号
TEL : 06-6531-2456 (代表) FAX : 06-6541-3198
E-mail : info@inagaki-shouten.jp <https://www.inagaki-shouten.jp>

2025.08